

Research Article

Design and Implementation of Light Fidelity (Li-Fi) System

Abhiraj Kumar^{1*}, Sagar Kumar², Om Prakash³, Ashish Tripathi⁴, Ashwani Kumar⁵, Dr. Zaiba Ishrat⁶, Vishal Chaudhary⁷, Tushar Pathak⁸

^{1,2,3}Student, ⁶Associate Professor^{4,5,7,8}Assistant Professor, Dept. of Electronics and Communication Engineering, Meerut Institute of Technology, Meerut, UP, India.

Received 01 Jan 2026, Accepted 12 Jan 2026, Available online 13 Jan 2026, Vol.16, No.1 (Jan/Feb 2026)

Abstract

Light Fidelity (Li-Fi) is an emerging wireless communication technology that uses visible light for high-speed data transmission instead of conventional radio frequency waves. With the rapid growth of wireless devices, radio spectrum congestion and security concerns have become major challenges. Li-Fi offers an effective solution by utilizing light emitted from Light Emitting Diodes (LEDs) to transmit data through rapid modulation that is imperceptible to the human eye. At the receiver end, a photodiode detects the light signals and converts them into electrical signals for data recovery. This project focuses on the design and implementation of a Li-Fi communication system that demonstrates secure, fast, and interference-free data transmission in indoor environments. Compared to traditional Wi-Fi systems, Li-Fi provides higher data rates, improved security, and immunity to electromagnetic interference, making it suitable for sensitive areas such as hospitals, aircraft cabins, and defense applications. The system is energy-efficient as it utilizes existing lighting infrastructure for communication. Li-Fi technology has the potential to revolutionize future wireless communication by enabling smart lighting, Internet of Things (IoT) integration, and high-density data networks. This project highlights the working principle, advantages, and practical significance of Li-Fi as a next-generation communication technology.

Keywords: Li-Fi Technology, Visible Light Communication, High-Speed Wireless Data, LED-Based Communication Systems

1. Introduction

Light Fidelity (Li-Fi) is a modern wireless communication technology that uses visible light as a medium for data transmission. With the rapid increase in the number of wireless devices, the conventional radio frequency spectrum used by Wi-Fi is becoming congested and prone to security and interference issues. Li-Fi overcomes these limitations by using light emitted from Light Emitting Diodes (LEDs) to transmit data at very high speeds. Since light cannot pass through walls, Li-Fi provides a more secure communication channel compared to traditional wireless technologies.

The basic working principle of Li-Fi is based on the fast switching of LED light intensity, which is not detectable by the human eye. The transmitted light signal is received by a photodiode, which converts it into an electrical signal for data processing. Li-Fi is especially useful in environments where radio frequency communication is restricted or unsafe, such as hospitals, airplanes, underwater communication, and defense sectors.

Due to its high data rate, low interference, enhanced security, and energy efficiency, Li-Fi is considered a promising technology for next generation wireless communication systems. This project aims to study the concept, working mechanism, and applications of Li-Fi technology.

2. Literature Survey

Light Fidelity (Li-Fi) technology has gained significant attention in recent years as an alternative to conventional wireless communication systems. The concept of Li-Fi was first introduced to overcome the limitations of radio frequency-based communication such as spectrum congestion, security issues, and electromagnetic interference. Researchers have demonstrated that visible light communication using Light Emitting Diodes (LEDs) can achieve very high data rates while maintaining energy efficiency. Several studies have focused on the fundamental working principle of Li-Fi, where data is transmitted through rapid modulation of LED light intensity and received using photodiodes. Experimental results show that Li-Fi can provide data rates comparable to or even higher than traditional Wi-Fi under controlled indoor

*Corresponding author's ORCID ID: 0000-0000-0000-0000
DOI: <https://doi.org/10.14741/ijcet/v.16.1.2>

environments. Researchers have also highlighted that Li-Fi offers enhanced security because light does not penetrate through walls, reducing the risk of unauthorized access.

Further research has explored the application of Li-Fi in sensitive environments such as hospitals, aircraft cabins, and industrial areas, where radio frequency communication may cause interference or safety hazards. Studies indicate that Li-Fi is immune to electromagnetic interference, making it suitable for such restricted zones. Integration of Li-Fi with smart lighting systems has also been widely discussed, showing its potential for smart homes, offices, and Internet of Things (IoT) applications.

Recent literature emphasizes the challenges of Li-Fi, including limited range, line-of-sight dependency, and performance degradation under ambient light conditions. However, ongoing research proposes solutions such as hybrid Li-Fi and Wi-Fi systems, advanced modulation techniques, and improved receiver sensitivity. Overall, the literature confirms that Li-Fi is a promising next-generation communication technology with vast potential for future wireless networks.

3. Application

1- High-Speed Indoor Communication – Li-Fi can be used in homes, offices, and classrooms to provide very high-speed wireless internet using LED lighting.

2- Hospitals and Healthcare – Li-Fi is suitable for hospitals because it does not cause electromagnetic interference with medical equipment.

3- Aircraft and Aviation – Li-Fi can be used inside aircraft cabins to provide safe and interference-free data communication for passengers.

4- Defense and Military Applications – Li-Fi offers secure communication since light does not pass through walls, making it useful for military and defense systems.

5- Smart Lighting Systems – Li-Fi can be integrated with LED lighting to transmit data while simultaneously providing illumination.

6- Industrial Automation – Li-Fi can be used in factories where radio frequency communication is restricted due to safety concerns.

7- Li-Fi is effective for underwater data transmission where radio waves and Wi-Fi do not work properly.

8- Smart Cities – Street lights equipped with Li-Fi can be used for traffic control, public internet access, and smart city applications.

9- Educational Institutions – Li-Fi can provide secure and high-speed internet in schools, colleges, and libraries.

10-Internet of Things (IoT) – Li-Fi supports high data density, making it suitable for IoT devices and smart environments.

11-Public Places – Li-Fi can be used in airports, railway stations, shopping malls, and museums for secure wireless communication.

12-Data Security Sensitive Areas – Li-Fi is ideal for banks, research labs, and government offices where secure data transmission is required.




Figure 1: Block diagram of Light Fidelity (Li-Fi) System

4. Hardware used

Arduino Uno

Arduino Uno is an open-source microcontroller board based on the ATmega328P microchip. It features 14 digital input/output pins, 6 analog inputs, a 16 MHz quartz crystal, a USB connection, and a power jack. The board is widely used in embedded system applications for prototyping, automation, and robotics due to its simplicity, low cost, and compatibility with the Arduino Integrated Development Environment (IDE) for easy programming and debugging.



Figure 2: Arduino Uno

LDR Sensor

An LDR, or Light Dependent Resistor, is a special type of resistor whose resistance changes depending on the amount of light falling on it. When there is bright light, the resistance of the LDR becomes very low, allowing more current to pass through the circuit. When there is darkness or very little light, its resistance becomes very high, which reduces the current flow. Because of this property, an LDR is commonly used in circuits that need to detect light levels, such as automatic street lights, brightness sensors, and light-based

communication systems like Li-Fi. In a Li-Fi receiver circuit, the LDR acts as a light sensor that detects the rapid variations in light intensity coming from the transmitting LED. These changes in light are converted into corresponding electrical signals, which can then be processed by an amplifier or microcontroller to recover the original data. Thus, the LDR plays an important role in converting optical signals into usable electrical information.



Figure 3: 16x2 LCD display

A 16x2 LCD display is an electronic screen that can show 16 characters per line and has 2 lines, which is why it is called "16x2." It is one of the most commonly used displays in electronic projects because it is easy to interface with microcontrollers like Arduino, PIC, or Raspberry Pi. The display uses Liquid Crystal Display (LCD) technology, where liquid crystals change their orientation when electricity is applied, allowing characters to appear on the screen. A 16x2 LCD usually works.



Figure 4: 16x2 LCD display

LED

In a Li-Fi data transfer system, an Android mobile flashlight can act as the transmitter because it is simply an LED light source controlled by the phone's hardware. When data is sent from the phone, the flashlight can be turned ON and OFF very quickly to represent digital information in the form of light pulses. Although the human eye cannot notice these rapid changes, a photodiode in the receiver circuit can detect them easily. The mobile phone uses specially designed apps that modulate the LED intensity according to the input data such as text, audio, or binary signals. These applications convert the digital information into a stream of ON-OFF light pulses using modulation techniques like On-Off Keying (OOK). As a result, the flashlight behaves as a high-speed optical transmitter, sending information through visible light without the use of radio frequency waves. This makes the LED an essential component in the Li-Fi system, enabling secure, interference-free, and energy-efficient wireless communication.

5. Result

The Light Fidelity (Li-Fi) communication system was successfully designed and tested under indoor conditions. The system effectively transmitted data using visible light from a high-brightness LED, and the receiver accurately detected the modulated light signal using a photodiode. The received signal was amplified and processed to reproduce the original information with minimal distortion. Experimental results showed stable and reliable data transmission within a limited line-of-sight range. The system performed efficiently in environments where radio frequency interference is present or restricted. It also demonstrated improved security, as the transmitted data remained confined to the illuminated area. The overall performance confirms that Li-Fi can serve as an effective alternative to traditional wireless communication for short-range indoor applications. The results validate the feasibility, simplicity, and practical usefulness of Li-Fi technology in modern communication systems.



Figure 5: LED

Conclusion

In this project, the design and implementation of a Light Fidelity (Li-Fi) communication system has been successfully presented. The system demonstrates the use of visible light for wireless data transmission using LEDs and a photodiode. Experimental results show that Li-Fi provides secure, fast, and interference-free communication within a short range. Since Li-Fi uses existing lighting infrastructure, it is energy-efficient and cost-effective. This project highlights the potential of Li-Fi as an alternative to traditional radio-frequency based wireless technologies, especially in indoor and sensitive environments. In the future, Li-Fi systems can be enhanced with advanced modulation techniques and hybrid integration with Wi-Fi to improve range, reliability, and data capacity.

Acknowledgement

I would like to express my sincere gratitude to my project guide for his valuable guidance, continuous support, and encouragement throughout the completion of this project. His technical suggestions

and motivation helped me to understand the concepts of Li-Fi technology in a better way. I am also thankful to the faculty members and laboratory staff of the Electronics and Communication Engineering department for providing the necessary facilities and resources. Finally, I would like to thank my family and friends for their constant support, cooperation, and motivation during the preparation of this project and research work.

References

- [1] Harald Haas, "Wireless Data from Every Light Bulb," TED Global Talk, 2011.
- [2] Harald Haas, Li-Fi: Visible Light Communication, IEEE Spectrum, 2013.
- [3] S. Dimitrov and H. Haas, Principles of LED Light Communications, Cambridge University Press, 2015.
- [4] Chun-Hao Yeh et al., "Visible Light Communication System," IEEE Photonics Journal, vol. 7, no. 2, 2015.
- [5] Rajagopal S., Roberts R., Lim S.K., "IEEE 802.15.7 Visible Light Communication," IEEE Standards, 2011.
- [6] Komine T. and Nakagawa M., "Fundamental Analysis for Visible-Light Communication System," IEEE Transactions on Consumer Electronics, vol. 50, no. 1, 2004.
- [7] P. H. Pathak et al., "Visible Light Communication, Networking, and Sensing," IEEE Communications Surveys & Tutorials, vol. 17, no. 4, 2015